

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 December 2003 (04.12.2003)

PCT

(10) International Publication Number
WO 03/100758 A1

(51) International Patent Classification⁷: **G09G 3/34**

(21) International Application Number: PCT/IB03/01992

(22) International Filing Date: 13 May 2003 (13.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02077017.8 24 May 2002 (24.05.2002) EP
02078823.8 16 September 2002 (16.09.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ZHOU, Guofu** [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **JOHNSON, Mark, T.** [GB/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **DEGUELLE, Wilhelmus, H., G.**; internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELECTROPHORETIC DISPLAY PANEL



(57) **Abstract:** The electrophoretic display panel (1) for displaying a picture, has a first and a second opposed substrate (8,9), an electrophoretic medium (5) between the substrates (8,9), a plurality of pixels (2), a first and a second electrode (3,4) associated with each pixel (2), drive means (100) and a temperature probe (11). The electrophoretic medium (5) has charged particles (6) in a fluid. The first and the second electrode (3,4) are able to receive a potential difference having a duration and a level. The drive means (100) are able to control the potential differences for displaying the picture, and the temperature probe (11) is able to measure a temperature indicative for the medium temperature. For the display panel (1) to be able to have pixels (2) with substantially reproducible appearances requiring relatively little energy independent of the ambient temperature, the drive means (100) are able to receive the measured temperature from the temperature probe (11) and to control the potential differences in dependence of the measured temperature.



WO 03/100758 A1

Electrophoretic display panel

The invention relates to an electrophoretic display panel for displaying a picture.

5 An embodiment of the electrophoretic display panel of the type mentioned in the opening paragraph is described in non-prepublished European Patent application 02078456.7 (PHNL020754).

10 In the described electrophoretic display panel, each pixel of the plurality of pixels has, during the display of the picture, an appearance determined by the position of the charged particles between the electrodes. The position of the particles depends on the potential difference as the particles migrate through the fluid as a consequence of the potential difference. The migration of the particles through the fluid also depends on the viscosity of the fluid. As the viscosity of the fluid is determined by the medium temperature, the position of the particles depends not only on the potential difference, but also on the
15 medium temperature. The display panel comprises heating means and is thereby able to have a predetermined substantially constant medium temperature above ambient temperature. As a result, the display panel is able to have pixels with substantially reproducible appearances at the predetermined medium temperature. The heating means heat the medium to the predetermined medium temperature, which may be relatively highly power consuming, e.g. if
20 the predetermined medium temperature is substantially higher than the ambient temperature. The predetermined medium temperature is chosen relatively high to be able to change the appearances of the pixels in a relatively short interval.

25 It is a drawback of the described display panel that it requires relatively high energy to obtain therewith pixels with substantially reproducible appearances independent of the ambient temperature.

 It is an object of the invention to provide a display panel of the kind mentioned in the opening paragraph which is able to have pixels with substantially reproducible

appearances requiring relatively little energy independent of the ambient temperature.

To achieve this object, the display panel in accordance with the invention is
5 specified in Claim 1.

The invention is based on the insight that, if the dependency of the
appearances of the pixels on the medium temperature is compensated for by the potential
differences, the appearances of the pixels are substantially reproducible. This dependency is
compensated for by the potential differences without the need for heating means regulating
10 the medium temperature. As relatively low power consuming electrical circuits can be used
to perform the compensation, the appearances of the pixels are substantially reproducible
requiring relatively little energy independent of the ambient temperature. As the drive means
are able to receive the measured temperature indicative for the medium temperature from the
temperature probe and to control the potential differences in dependence of the measured
15 temperature, the display panel is able to have pixels with substantially reproducible
appearances requiring relatively little energy independent of the ambient temperature.
This is in contrast to the display panel described in non-prepublished European Patent
application 02078456.7 (PHNL020754) which requires, due to the relatively high power
consuming heating means, relatively high energy to have pixels with substantially
20 reproducible appearances if the predetermined medium temperature is maintained at a
substantially higher level than the ambient temperature. Furthermore, the prior art display
panel does not have pixels with substantially reproducible appearances at an ambient
temperature above the predetermined medium temperature, because the heating means are
unable to cool the medium to the predetermined medium temperature.

25

In an embodiment the drive means are able to control the durations in
dependence of the measured temperature. The durations are relatively short if the medium is
able to change relatively fast between two appearances and relatively long if the medium is
30 only able to change relatively slow between two appearances. For instance, as the medium at
60 °C is able to change faster between two appearances than at 20 °C, the durations at the
higher temperature are shorter than the durations at the lower temperature.

In a modification of the last embodiment the drive means are able to control
each duration to consist of a number of intervals of equal time period, the number being

determined by the picture to be displayed and the measured temperature, and the time period being constant. Then only the number of intervals has a different value if the measured temperature has changed.

5 In another modification of the last embodiment the drive means are able to control each duration to consist of a number of intervals of equal time period, the number being determined by the picture to be displayed and the time period being determined by the measured temperature. Then only the time period has a different value if the measured temperature has changed.

10 In another embodiment the drive means are able to control the levels in dependence of the measured temperature. The levels are relatively low if the medium is able to change relatively fast between two appearances and relatively high if the medium is only able to change relatively slow between two appearances. For instance, as the medium having a temperature of 60 °C is able to change faster between two appearances than the medium having a temperature of 20 °C, the levels at the higher temperature are shorter than the levels
15 at the lower temperature.

If the first substrate comprises the first electrodes, and the second substrate comprises the second electrodes, the appearances of the pixels can relatively easy be changed compared to the display panel having one of the substrates comprising the first and the second electrode.

20

These and other aspects of the display panel of the invention will be further elucidated and described with reference to the drawings, in which:

25 Figure 1 shows diagrammatically a front view of a first embodiment of the display panel;

Figure 2 shows diagrammatically a cross-sectional view along II-II in Figure 1;

Figure 3 shows in a graphical form the relation between the measured temperature and the durations for the first embodiment; and

30 Figure 4 shows in a graphical form the relation between the measured temperature and the levels for a second embodiment.

In all the Figures corresponding parts are referenced to by the same reference numerals.

Figures 1 and 2 show the first embodiment of the display panel 1 having a second substrate 9 and a plurality of pixels 2. The pixels 2 are arranged along substantially straight lines in a two-dimensional structure. Other arrangements of the pixels 2 are also possible, e.g. a honeycomb arrangement. The display panel 1 has a first substrate 8 and a second opposed substrate 9. An electrophoretic medium 5 is present between the substrates 8,9. The electrophoretic medium 5 comprises for instance negatively charged black particles 6 in a white fluid. Electrophoretic media are known per se from e.g. US 5,961,804, US 6,120,839 and US 6,130,774 and can e.g. be obtained from E Ink Corporation. A first and a second electrode 3,4 are associated with each pixel 2. The electrodes 3,4 are able to receive a potential difference. In Figure 2 the first substrate 8 has for each pixel 2 a first electrode 3, and the second substrate 9 has for each pixel 2 a second electrode 4. When the charged particles 6 are positioned near the first electrode 3 due to a potential difference having a level of 15 Volts, the pixel 2 has a first appearance, i.e. white. When the charged particles 6 are positioned near the second electrode 4, due to a potential difference of opposite polarity, having a level of -15 Volts, the pixel 2 has a second appearance, i.e. black. A temperature probe 11, e.g. present on the surface of the first substrate 8 facing the medium, is able to measure a temperature indicative for the medium temperature. Furthermore, the drive means 100 are able to control the potential differences for displaying the picture, to receive the measured temperature from the temperature probe 11, and to control the potential differences in dependence of the measured temperature.

Figure 3 shows the relation between the measured temperature and the durations of the potential differences for the first embodiment. The levels of the potential differences are 15 Volts. The distance between the electrodes 3,4 is about 80 micrometer. The layer of electrophoretic medium 5 has a thickness of about 50 micrometer. Furthermore, a layer of polymer binder material having a thickness of about 30 micrometer is present between the electrodes 3,4. The line 'a' is related to a change in appearance of the pixel from black to white, denoted as transition B-W, and the line 'b' is related to a change in appearance of the pixel from dark gray to light gray, denoted as transition DG-LG. The durations decrease with increasing measured temperature. In the first embodiment the drive means 100 are able to control durations of the potential differences in dependence of the measured temperature according to Figure 3. Therefore, the dependency of the appearances of the pixels on the medium temperature is compensated for by the potential differences and the display panel 1 is able to have pixels 2 with substantially reproducible appearances

requiring relatively little energy independent of the ambient temperature. The relation between the measured temperature and the durations may be incorporated in the drive means 100 by means of a look-up-table. Furthermore, Figure 3 shows that the duration of the transition B-W is substantially proportional to the duration of the transition DG-LG.

5 Therefore, in a variation of the first embodiment the drive means 100 are able to control each duration to consist of a number of intervals of equal time period, the number being determined by the picture to be displayed and the measured temperature, and the time period being constant. In another variation of the first embodiment the drive means 100 are able to control each duration to consist of a number of intervals of equal time period, the number
10 being determined by the picture to be displayed and the time period being determined by the measured temperature.

Figure 4 shows the relation between the measured temperature and the levels of the potential differences for a second embodiment. The durations of the potential differences are 200 ms. The distance between the electrodes 3,4 is about 80 micrometer. The
15 layer of electrophoretic medium 5 has a thickness of about 50 micrometer. Furthermore, a layer of polymer binder material having a thickness of about 30 micrometer is present between the electrodes 3,4. The relation is related to the transition B-W. The levels decrease with increasing measured temperature. In the second embodiment the drive means 100 are able to control levels of the potential differences in dependence of the measured temperature
20 according to Figure 4. The relation between the measured temperature and the levels may be incorporated in the drive means 100 by means of a look-up-table.

CLAIMS:

1. An electrophoretic display panel for displaying a picture, comprising:
 - a first and a second opposed substrate;
 - an electrophoretic medium between the substrates, the electrophoretic medium comprising charged particles in a fluid;
 - 5 - a plurality of pixels;
 - a first and a second electrode associated with each pixel for receiving a potential difference having a duration and a level;
 - drive means being able to control the potential differences for displaying the picture; and
 - a temperature probe being able to measure a temperature indicative for a medium
 - 10 temperature, wherein
 - the drive means are further able to receive the measured temperature from the temperature probe and to control the potential differences in dependence of the measured temperature.
2. A display panel as claimed in claim 1 characterized in that the drive means are
- 15 able to control the durations in dependence of the measured temperature.
3. A display panel as claimed in claim 2 characterized in that the drive means are
- able to control each duration to consist of a number of intervals of equal time period, the
- number being determined by the picture to be displayed and the measured temperature, and
- 20 the time period being constant.
4. A display panel as claimed in claim 2 characterized in that the drive means are
- able to control each duration to consist of a number of intervals of equal time period, the
- number being determined by the picture to be displayed and the time period being determined
- 25 by the measured temperature.
5. A display panel as claimed in claim 1 characterized in that the drive means are
- able to control the levels in dependence of the measured temperature.

6. A display panel as claimed in any one of the preceding claims, characterized in that the first substrate comprises the first electrodes, and the second substrate comprises the second electrodes.

1/2




FIG. 1




FIG. 2

2/2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/01992

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G09G3/34

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G09G G02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 947 159 A (DI SANTO FRANK J ET AL) 7 August 1990 (1990-08-07) the whole document	1,2,5,6
Y	DALISA A L: "ELECTROPHORETIC DISPLAYS" DISPLAY DEVICES, TOPICS IN APPLIED PHYSICS, BERLIN, SPRINGER VERLAG, DE, vol. 40, 1980, pages 213-232, XP002065449 the whole document	1,2,5,6
Y	US 4 367 469 A (HASHIMOTO SADAKATSU) 4 January 1983 (1983-01-04) the whole document	1,5,6

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

° Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

4 August 2003

Date of mailing of the international search report

25/08/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Harke, M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/01992

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WILLIAMS M: "PRACTICAL 5-LEVEL LCD MULTIPLEXING" WESCON CONFERENCE RECORD, XX, XX, 16 September 1980 (1980-09-16), pages 28-401-28-408, XP000676220 the whole document ----	1,5,6
Y	US 5 033 822 A (INOUE HIROSHI ET AL) 23 July 1991 (1991-07-23) the whole document ----	1,2,5,6
Y	EP 1 079 361 A (HARNESS SYST TECH RES LTD ;SUMITOMO WIRING SYSTEMS (JP); SUMITOMO) 28 February 2001 (2001-02-28) the whole document -----	1,2,5,6

INTERNATIONAL SEARCH REPORT

Inter
PCT/IB 03/01992

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4947159	A	07-08-1990	NONE	
US 4367469	A	04-01-1983	JP 56012692 A	07-02-1981
US 5033822	A	23-07-1991	JP 2096117 A JP 2614280 B2	06-04-1990 28-05-1997
EP 1079361	A	28-02-2001	JP 2001056661 A JP 2001100698 A JP 2001117535 A EP 1079361 A1	27-02-2001 13-04-2001 27-04-2001 28-02-2001